

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 1751

UNUSUAL FIRE AND EXPLOSION HAZARDS: Exposure to temperatures above 120 deg.F may cause bursting.

===== SECTION V - REACTIVITY DATA =====

STABILITY: Product is stable under normal conditions.

CONDITIONS TO AVOID: Open flame, sparks, or high temperature.

INCOMPATIBILITY (MATERIALS TO AVOID): Acids, alkalis, oxidizing materials.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Thermal decomposition and or burning may produce oxides of carbon, HCl gas, Phosgene.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

===== SECTION VI - HEALTH HAZARD DATA =====

PRIMARY ROUTES OF ENTRY: Inhalation X Eye Contact X
Skin Contact X Ingestion

EXPOSURE LIMIT: Refer to Section II for PEL / TLV exposure limits.

ACUTE EFFECTS OF OVEREXPOSURE

INHALATION: Inhalation of mist can cause irritation of nasal and respiratory passages. Abusive or excessive inhalation may cause irritation to upper respiratory tract, dizziness, nausea and other central nervous system effects.

EYE CONTACT: Vapors may be irritating. Direct contact of product with eye may cause moderate irritation with corneal injury.

SKIN CONTACT: May cause skin irritation on repeated or prolonged contact.

SKIN ABSORPTION: Can be irritating to skin

INGESTION: Can cause gastrointestinal irritation, nausea, vomiting, and diarrhea. Aspiration of product into lungs can cause chemical pneumonia.

CHRONIC EFFECTS OF OVEREXPOSURE: Product contains methylene chloride, which has been determined by the State of California to have reproductive toxicity. Women who are pregnant should especially take note of this caution.

CARCINOGENICITY: NTP CARCINOGEN: IARC MONOGRAPHS: OSHA REGULATED: X

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY OVEREXPOSURE: No additional effects of overexposure to this material can be found from available information.

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: Remove to fresh air. If breathing has stopped give artificial respiration. Get IMMEDIATE MEDICAL ATTENTION

EYE CONTACT: Immediately flush eyes with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately.

SKIN CONTACT: Wash exposed area thoroughly with soap and water. Consult a physician if irritation develops.

INGESTION: Do not induce vomiting. Seek medical attention immediately.

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 1751

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove all ignition sources. Avoid breathing vapors. Shut off source of spill if it can be done safely. Use non-sparking tools. Absorb with inert, absorbant material and dispose of in accordance with applicable regulations.

WASTE DISPOSAL METHOD: Dispose of in accordance with applicable Federal, State, and local regulations. Under RCRA regulations, it is the responsibility of the product user to determine, at the time of disposal, whether a material is hazardous.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Store in a dry, cool place away from heat or open flame. Do not store at temperatures above 120 F.

OTHER PRECAUTIONS: Follow label instructions. KEEP OUT OF REACH OF CHILDREN.

===== SECTION VIII - PERSONEL SAFETY MEASURES =====

RESPIRATORY PROTECTION: Wear an appropriate, properly-fitted respirator (NIOSH/MSHA approved) during and after application unless air monitoring demonstrates that vapor/mist levels are below applicable limits. Follow respirator manufacturer's directions for respirator use.

VENTILATION: Use with adequate ventilation. Provide general local exhaust ventilation to keep the air contaminant concentration below the applicable exposure limit (OSHA PEL) of the combined components listed in Section II and below the LEL in Section IV.

PROTECTIVE GLOVES: Impervious gloves recommended.

EYE PROTECTION: Safety eye protection to protect against splash of liquids and also aerosol size particles is recommended.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Synthetic apron to protect against splash of liquids.

WORK/HYGIENIC PRACTICES: Wash thoroughly after handling.

===== SECTION IX - REGULATORY INFORMATION =====

TOXIC SUBSTANCES CONTROL ACT (TSCA): All chemical components in this product are listed on the TSCA Inventory List, or are exempt from listing.

SARA Section 312 HAZARD CATEGORIES: Fire Hazard X Reactivity Hazard

Acute Health Hazard X Chronic Health Hazard X Pressure Hazard X

SARA Section 313 REPORTABLE COMPONENTS: (See Section II, If Applicable)

===== SECTION X - SHIPPING INFORMATION =====

DOT SHIPPING NAME: ORM-D Consumer Commodity

DOT HAZARD CLASS: Not Applicable

UN NUMBER: Not Applicable

DOT PACKING GROUP: Not Applicable

SPECIAL SHIPPING INFORMATION: Regulated only when offered for transportation by aircraft.

===== DISCLAIMER =====

The information on this Material Safety Data Sheet represents our current available data and best opinion as to the proper handling in use of this product under normal conditions. Any use of this product which is not in conformance with this Data Sheet or which involves using this product in combination with other materials, or processes is the sole responsibility of the user.

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 1750

UNUSUAL FIRE AND EXPLOSION HAZARDS: A straight stream of water will spread the fire. A vapor accumulation will flash and or explode if ignited. Cool the containers with water spray or fog. Empty containers may also present a fire or explosion hazard due to accumulation of residual vapors

===== SECTION V - REACTIVITY DATA =====

STABILITY: Product is stable under normal conditions.

CONDITIONS TO AVOID: Open flame, sparks, or high temperature.

INCOMPATIBILITY (MATERIALS TO AVOID): Acids, alkalies, oxidizing materials.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Thermal decomposition and or burning may produce oxides of carbon, HCl gas, Phosgene.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

===== SECTION VI - HEALTH HAZARD DATA =====

PRIMARY ROUTES OF ENTRY: Inhalation X Eye Contact X
Skin Contact X Ingestion X

EXPOSURE LIMIT: Refer to Section II for PEL / TLV exposure limits.

ACUTE EFFECTS OF OVEREXPOSURE

INHALATION: Inhalation of mist can cause irritation of nasal and respiratory passages. Abusive or excessive inhalation may cause irritation to upper respiratory tract, dizziness, nausea and other central nervous system effects.

EYE CONTACT: Vapors may be irritating. Direct contact of product with eye may cause moderate irritation with corneal injury.

SKIN CONTACT: May cause skin irritation on repeated or prolonged contact.

SKIN ABSORPTION: Can be irritating to skin

INGESTION: Can cause gastrointestinal irritation, nausea, vomiting, and diarrhea. Aspiration of product into lungs can cause chemical pneumonia.

CHRONIC EFFECTS OF OVEREXPOSURE: Product contains methylene chloride, which has been determined by the State of California to have reproductive toxicity. Women who are pregnant should especially take note of this caution.

CARCINOGENICITY: NTP CARCINOGEN: IARC MONOGRAPHS: OSHA REGULATED: X

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY OVEREXPOSURE: No additional effects of overexposure to this material can be found from available information.

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: Remove to fresh air. If breathing has stopped give artificial respiration. Get IMMEDIATE MEDICAL ATTENTION

EYE CONTACT: Immediately flush eyes with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately.

SKIN CONTACT: Wash exposed area thoroughly with soap and water. Consult a physician if irritation develops.

INGESTION: Do not induce vomiting. Seek medical attention immediately.

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 1750

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove all ignition sources. Avoid breathing vapors. Shut off source of spill if it can be done safely. Use non-sparking tools. Absorb with inert, absorbant material and dispose of in accordance with applicable regulations.

WASTE DISPOSAL METHOD: Dispose of in accordance with applicable Federal, State, and local regulations. Under RCRA regulations, it is the responsibility of the product user to determine, at the time of disposal, whether a material is hazardous.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Do not store above 120 F. Keep closure tight and container upright to prevent leakage. Store drum out of sunlight and away from heat, sparks, or flame. Store only in well-ventilated areas.

OTHER PRECAUTIONS: Follow label instructions. KEEP OUT OF REACH OF CHILDREN.

===== SECTION VIII - PERSONEL SAFETY MEASURES =====

RESPIRATORY PROTECTION: Wear an appropriate, properly-fitted respirator (NIOSH/MSHA approved) during and after application unless air monitoring demonstrates that vapor/mist levels are below applicable limits. Follow respirator manufacturer's directions for respirator use.

VENTILATION: Use with adequate ventilation. Provide general local exhaust ventilation to keep the air contaminant concentration below the applicable exposure limit (OSHA PEL) of the combined components listed in Section II and below the LEL in Section IV.

PROTECTIVE GLOVES: Impervious gloves recommended.

EYE PROTECTION: Use safety eyewear designed to protect against splash of liquids.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Synthetic apron to protect against splash of liquids.

WORK/HYGIENIC PRACTICES: Wash thoroughly after handling.

===== SECTION IX - REGULATORY INFORMATION =====

TOXIC SUBSTANCES CONTROL ACT (TSCA): All chemical components in this product are listed on the TSCA Inventory List, or are exempt from listing.

SARA Section 312 HAZARD CATEGORIES: Fire Hazard X Reactivity Hazard

Acute Health Hazard X Chronic Health Hazard X Pressure Hazard

SARA Section 313 REPORTABLE COMPONENTS: (See Section II, If Applicable)

===== SECTION X - SHIPPING INFORMATION =====

DOT SHIPPING NAME: Flammable Liquid, n.o.s. (contains Toluene)

DOT HAZARD CLASS: Class 3

UN NUMBER: UN 1993

DOT PACKING GROUP: Group II

SPECIAL SHIPPING INFORMATION: Not Applicable

===== DISCLAIMER =====

The information on this Material Safety Data Sheet represents our current available data and best opinion as to the proper handling in use of this product under normal conditions. Any use of this product which is not in conformance with this Data Sheet or which involves using this product in combination with other materials, or processes is the sole responsibility of the user.