

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 2520

===== SECTION V - REACTIVITY DATA =====

STABILITY: Product is stable under normal conditions.

CONDITIONS TO AVOID: Open flame, sparks, or high temperature.

INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizing agents.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Thermal decomposition and burning may produce carbon dioxide and carbon monoxide.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

===== SECTION VI - HEALTH HAZARD DATA =====

PRIMARY ROUTES OF ENTRY: Inhalation X Eye Contact X
Skin Contact X Ingestion

EXPOSURE LIMIT: Refer to Section II for PEL / TLV exposure limits.

ACUTE EFFECTS OF OVEREXPOSURE

INHALATION: Excessive inhalation of high vapor concentrations may cause upper respiratory tract irritation, sleepiness and/or dizziness.

EYE CONTACT: Eye irritant. May cause injury if left untreated.

SKIN CONTACT: May cause skin irritation on repeated or prolonged contact.

SKIN ABSORPTION: Prolonged or repeated contact with the skin may cause defatting and irritation.

INGESTION: Harmful if swallowed. Can cause mouth, throat, and gastrointestinal tract irritation, nausea, vomiting, and diarrhea. Aspiration of material into the lungs can cause chemical pneumonitis which can be fatal.

CHRONIC EFFECTS OF OVEREXPOSURE: Chronic effects and medical conditions aggravated by overexposure to this product have not been established. Unnecessary exposure to this product or any chemical should be avoided.

CARCINOGENICITY: NTP CARCINOGEN: IARC MONOGRAPHS: OSHA REGULATED:

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY OVEREXPOSURE: No additional effects of overexposure to this material can be found from available information.

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: Remove to fresh air immediately. If person experiences nausea, headache, dizziness, or has difficulty breathing, get medical attention immediately.

EYE CONTACT: IN CASE OF CONTACT: Immediately flush eyes with plenty of water for at least 15 minutes. Consult a physician. Wash skin with soap and water.

SKIN CONTACT: In case of contact, immediately flush skin with soap and water.

INGESTION: IF SWALLOWED: Call a physician immediately. Do NOT induce vomiting unless directed to do so by a physician. Never give anything by mouth to an unconscious person.

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 2520

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove all ignition sources. Avoid breathing vapors. Shut off source of spill if it can be done safely. Use non-sparking tools. Absorb with inert, absorbant material and dispose of in accordance with applicable regulations.

WASTE DISPOSAL METHOD: Dispose of in accordance with applicable Federal, State, and local regulations. Under RCRA regulations, it is the responsibility of the product user to determine, at the time of disposal, whether a material is hazardous.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Do not store above 120 F. Keep closure tight and container upright to prevent leakage. Store drum out of sunlight and away from heat, sparks, or flame. Store only in well-ventilated areas.

OTHER PRECAUTIONS: Follow label instructions. KEEP OUT OF REACH OF CHILDREN.

===== SECTION VIII - PERSONEL SAFETY MEASURES =====

RESPIRATORY PROTECTION: None required in excess of normal ventilation.

VENTILATION: Local mechanical exhaust to provide normal ventilation.

PROTECTIVE GLOVES: Not required, but contact with skin must be avoided.

EYE PROTECTION: Use safety eyewear designed to protect against splash of liquids.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: None required.

WORK/HYGIENIC PRACTICES: Wash thoroughly after handling.

===== SECTION IX - REGULATORY INFORMATION =====

TOXIC SUBSTANCES CONTROL ACT (TSCA): All chemical components in this product are listed on the TSCA Inventory List, or are exempt from listing.

SARA Section 312 HAZARD CATEGORIES: Fire Hazard X Reactivity Hazard

Acute Health Hazard X Chronic Health Hazard Pressure Hazard

SARA Section 313 REPORTABLE COMPONENTS: (See Section II, If Applicable)

===== SECTION X - SHIPPING INFORMATION =====

DOT SHIPPING NAME: Flammable Liquids, n.o.s. (contains Terpene Hydrocarbons)

DOT HAZARD CLASS: Class 3

UN NUMBER: UN 1993

DOT PACKING GROUP: Group III

SPECIAL SHIPPING INFORMATION: Except gallon sizes or less than gallon sizes.

===== DISCLAIMER =====

The information on this Material Safety Data Sheet represents our current available data and best opinion as to the proper handling in use of this product under normal conditions. Any use of this product which is not in conformance with this Data Sheet or which involves using this product in combination with other materials, or processes is the sole responsibility of the user.