

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 2625

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Thermal decomposition and burning may produce carbon dioxide and carbon monoxide.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

===== SECTION VI - HEALTH HAZARD DATA =====

PRIMARY ROUTES OF ENTRY: Inhalation X Eye Contact X
Skin Contact X Ingestion X

EXPOSURE LIMIT: Refer to Section II for PEL / TLV exposure limits.

ACUTE EFFECTS OF OVEREXPOSURE

INHALATION: May cause nose, throat, and lung irritation.

EYE CONTACT: May cause permanent eye injury or blindness.

SKIN CONTACT: Causes moderate to severe burns which may not be immediately painful or visible.

SKIN ABSORPTION: Product is very corrosive to skin.

INGESTION: Ingestion will cause burns to mouth, throat and stomach and can cause death.

CHRONIC EFFECTS OF OVEREXPOSURE: Prolonged exposures may result in upper respiratory irritation and ulceration of the nasal passage. High levels may cause permanent lung injury.

CARCINOGENICITY: NTP CARCINOGEN: IARC MONOGRAPHS: OSHA REGULATED:

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY OVEREXPOSURE: May aggravate existing eye, skin, or upper respiratory conditions.

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: Remove to fresh air. If breathing has stopped give artificial respiration. Get IMMEDIATE MEDICAL ATTENTION

EYE CONTACT: Flush eyes with cool running water for 15 minutes while calling for IMMEDIATE MEDICAL ATTENTION. Washing eyes within several seconds is essential to achieve maximum effectiveness.

SKIN CONTACT: In case of contact, immediately flush skin with soap and plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Wash and thoroughly clean contaminated clothing and shoes before reuse. Get medical attention.

INGESTION: NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. If swallowed, DO NOT INDUCE VOMITING. Give large quantities of water. (If available, give several glasses of milk.) GET MEDICAL ATTENTION IMMEDIATELY.

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 2625

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Stop source of spill if it can be done safely. Wear splash- proof eye protection, impervious gloves and boots, and protective clothing. Absorb spill onto absorbent material and dispose of according to applicable regulations. Do not allow spills or runoff

WASTE DISPOSAL METHOD: Dispose of in accordance with applicable Federal, State, and local regulations. Under RCRA regulations, it is the responsibility of the product user to determine, at the time of disposal, whether a material is hazardous.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Do not store above 120 F. Keep closure tight and container upright to prevent leakage. Store drum out of sunlight and away from heat, sparks, or flame. Store only in well-ventilated areas.

OTHER PRECAUTIONS: Follow label instructions. KEEP OUT OF REACH OF CHILDREN.

===== SECTION VIII - PERSONEL SAFETY MEASURES =====

RESPIRATORY PROTECTION: Wear an appropriate, properly fitted vapor respirator during application of this product in a confined space.

VENTILATION: Local mechanical exhaust to provide normal ventilation.

PROTECTIVE GLOVES: Alkali-resistant gloves should be worn whenever handling this material.

EYE PROTECTION: Both chemical goggles and full face shield are recommended. Contact lenses should not be worn.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Eyewash, safety shower, impervious clothing and boots.

WORK/HYGIENIC PRACTICES: Wash thoroughly after handling.

===== SECTION IX - REGULATORY INFORMATION =====

TOXIC SUBSTANCES CONTROL ACT (TSCA): All chemical components in this product are listed on the TSCA Inventory List, or are exempt from listing.

SARA Section 312 HAZARD CATEGORIES: Fire Hazard___ Reactivity Hazard_X

Acute Health Hazard_X Chronic Health Hazard_X Pressure Hazard___

SARA Section 313 REPORTABLE COMPONENTS: (See Section II, If Applicable)

===== SECTION X - SHIPPING INFORMATION =====

DOT SHIPPING NAME: Corrosive Liquids, n.o.s. (contains Sodium Hydroxide)

DOT HAZARD CLASS: Class 8

UN NUMBER: UN 1760

DOT PACKING GROUP: Group II

SPECIAL SHIPPING INFORMATION: Not Applicable

===== DISCLAIMER =====

The information on this Material Safety Data Sheet represents our current available data and best opinion as to the proper handling in use of this product under normal conditions. Any use of this product which is not in conformance with this Data Sheet or which involves using this product in combination with other materials, or processes is the sole responsibility of the user.