

M A T E R I A L S A F E T Y D A T A S H E E T

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 6605

PRODUCT NAME: PURSUIT-94
 PRODUCT CODE: 6605

HMIS CODES: H C F R P
 1 0 0 B

WHMIS CLASS: Not a Controlled Product

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: ATCO International
 ADDRESS : 2136 Kingston Court
 Marietta, GA 30067-8902
 INFORMATION PHONE : (770)424-7550

DATE PRINTED: 02/06/2007

PREPARED BY: MAURICIO A. AMAYA, DIRECTOR OF TECHNICAL SERVICES
 REVISION DATE: 08/01/2005

===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	PEL	TLV	WEIGHT PERCENT
1,2 - propanediol	57-55-6	ND	ND	10-15%
Bacterial Spore Concentrate	68920-42-3	ND	ND	5-15%

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: >212 F SPECIFIC GRAVITY (H2O=1): 1.01
 VAPOR DENSITY: ND EVAPORATION RATE: ND
 DENSITY: 8.44 lb/gl MATERIAL V.O.C.: ND
 SOLUBILITY IN WATER: COMPLETELY SOLUBLE pH (Concentrate): 7.5
 APPEARANCE: SLIGHTLY TURBID TO CLEAR TAN LIQUID pH (Diluted): 7-9
 ODOR: SWEET.

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

OSHA FLAMMABILITY CLASSIFICATION: NOT REGULATED
 FLASH POINT: >212 F METHOD USED: Estimate
 FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: ND UPPER: ND

EXTINGUISHING MEDIA: Chemical foam. Does not ignite readily.

SPECIAL FIREFIGHTING PROCEDURES: If water is used, fog nozzles are preferable. Water may be used to cool closed containers in order to prevent pressure build up which may result in an explosion.

UNUSUAL FIRE AND EXPLOSION HAZARDS: None.

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 6605

===== SECTION V - REACTIVITY DATA =====

STABILITY: Product is stable under normal conditions.

CONDITIONS TO AVOID: None known.

INCOMPATIBILITY (MATERIALS TO AVOID): Strong acids may inactivate cultures.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: None known.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

===== SECTION VI - HEALTH HAZARD DATA =====

PRIMARY ROUTES OF ENTRY: Inhalation _____ Eye Contact X
Skin Contact X Ingestion X

EXPOSURE LIMIT: Refer to Section II for PEL / TLV exposure limits.

ACUTE EFFECTS OF OVEREXPOSURE

INHALATION: Essentially non irritating.

EYE CONTACT: May cause eye irritation.

SKIN CONTACT: May cause skin irritation on repeated or prolonged contact.

SKIN ABSORPTION: Bacterial infection may occur through wounds or broken skin.

INGESTION: May cause nausea or diarrhea if ingested.

CHRONIC EFFECTS OF OVEREXPOSURE: Chronic effects and medical conditions aggravated by overexposure to this product have not been established. Unnecessary exposure to this product or any chemical should be avoided.

CARCINOGENICITY: NTP CARCINOGEN: _____ IARC MONOGRAPHS: _____ OSHA REGULATED: _____

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY OVEREXPOSURE: No additional effects of overexposure to this material can be found from available information.

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: Remove to fresh air immediately. If person experiences nausea, headache, dizziness, or has difficulty breathing, get medical attention immediately.

EYE CONTACT: IN CASE OF CONTACT: Immediately flush eyes with plenty of water for at least 15 minutes. Consult a physician.

SKIN CONTACT: In case of contact, wash skin with soap and water.

INGESTION: IF SWALLOWED, Do not induce vomiting. Drink 2 glasses of water and consult a physician.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Stop source of spill. Absorb with inert absorbant material and dispose of in a manner consistent with applicable regulations.

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 6605

WASTE DISPOSAL METHOD: Dispose of in accordance with applicable Federal, State, and local regulations. Under RCRA regulations, it is the responsibility of the product user to determine, at the time of disposal, whether a material is hazardous.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Do not store above 120 F. Keep closure tight and container upright to prevent leakage. Store drum out of sunlight and away from heat. Store only in well-ventilated areas.

OTHER PRECAUTIONS: Follow label instructions. KEEP OUT OF REACH OF CHILDREN.

===== SECTION VIII - PERSONEL SAFETY MEASURES =====

RESPIRATORY PROTECTION: None required in excess of normal ventilation.

VENTILATION: Local mechanical exhaust to provide normal ventilation.

PROTECTIVE GLOVES: Impervious gloves recommended.

EYE PROTECTION: Use safety eyewear designed to protect against splash of liquids.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: None required.

WORK/HYGIENIC PRACTICES: Wash thoroughly after handling.

===== SECTION IX - REGULATORY INFORMATION =====

TOXIC SUBSTANCES CONTROL ACT (TSCA): All chemical components in this product are listed on the TSCA Inventory List, or are exempt from listing.

SARA Section 312 HAZARD CATEGORIES: Fire Hazard___ Reactivity Hazard___

Acute Health Hazard_X Chronic Health Hazard___ Pressure Hazard___

SARA Section 313 REPORTABLE COMPONENTS: (See Section II, If Applicable)

===== SECTION X - SHIPPING INFORMATION =====

DOT SHIPPING NAME: Cleaning Compound - liquid

DOT HAZARD CLASS: Not Applicable

UN NUMBER: Not Applicable

DOT PACKING GROUP: Not Applicable

SPECIAL SHIPPING INFORMATION: Not Applicable

===== DISCLAIMER =====

The information on this Material Safety Data Sheet represents our current available data and best opinion as to the proper handling in use of this product under normal conditions. Any use of this product which is not in conformance with this Data Sheet or which involves using this product in combination with other materials, or processes is the sole responsibility of the user.