

M A T E R I A L S A F E T Y D A T A S H E E T

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 4035

PRODUCT NAME: QUICK-SAN II
 PRODUCT CODE: 4035

HMIS CODES: H C F R P
 1 3 0 A

WHMIS CLASS: Not Determined

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: ATCO International
 ADDRESS : 2136 Kingston Court
 Marietta, GA 30067-8902
 INFORMATION PHONE : (770)424-7550

DATE PRINTED: 03/08/2007

PREPARED BY: MAURICIO A. AMAYA, DIRECTOR OF TECHNICAL SERVICES
 REVISION DATE: 01/31/2007

===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	PEL	TLV	WEIGHT PERCENT
ETHYL ALCOHOL	64-17-5	1000ppm	1000ppm	35-45%
Glycerin	56-81-5	ND	ND	1-3%
Triclosan	3380-34-5	ND	ND	<1%

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: >150 DEG. F SPECIFIC GRAVITY (H2O=1): 0.90
 VAPOR DENSITY: ND EVAPORATION RATE: ND
 DENSITY: 7.506 lb/gl MATERIAL V.O.C.: ND
 SOLUBILITY IN WATER (of Conc. Liquid): COMPLETE pH (Concentrate): ND
 APPEARANCE: WHITE TOWEL IMPREGNATED W/ CLEAR LIQUID pH (Diluted): ND
 ODOR: WINTERGREEN.

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

OSHA FLAMMABILITY CLASSIFICATION: CLASS IC METHOD USED: TCC
 FLASH POINT: 80 F (CONC. ONLY) UPPER: ND
 FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: ND

EXTINGUISHING MEDIA: Water fog, Carbon dioxide, Dry chemical, or Foam.

SPECIAL FIREFIGHTING PROCEDURES: Use self contained breathing apparatus with a full face piece operated in the positive pressure demand mode. Chemical resistant Personal Protective Equipment is recommended.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Contains ethyl alcohol. Vapors may ignite if allowed to accumulate.

===== SECTION V - REACTIVITY DATA =====

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 4035

STABILITY: Product is stable under normal conditions.

CONDITIONS TO AVOID: Open flame, sparks, or high temperature.

INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizing agents.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Thermal decomposition and burning may produce carbon dioxide and carbon monoxide.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

===== SECTION VI - HEALTH HAZARD DATA =====

PRIMARY ROUTES OF ENTRY: Inhalation X Eye Contact X
Skin Contact Ingestion

EXPOSURE LIMIT: Refer to Section II for PEL / TLV exposure limits.

ACUTE EFFECTS OF OVEREXPOSURE

INHALATION: None known.

EYE CONTACT: May cause stinging of eyes followed by irritation.

SKIN CONTACT: May cause dryness with prolonged contact.

SKIN ABSORPTION: No evidence of adverse effects from available information.

INGESTION: May cause dizziness, faintness, drowsiness, decreased awareness and responsiveness, lack of coordination, abdominal discomfort, nausea, vomiting and diarrhea.

CHRONIC EFFECTS OF OVEREXPOSURE: Repeated or prolonged exposure to ethanol can be irritating to mucosal membranes.

CARCINOGENICITY: NTP CARCINOGEN: IARC MONOGRAPHS: OSHA REGULATED:

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY OVEREXPOSURE: No evidence of adverse effects from available information.

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.

EYE CONTACT: Immediately flush eyes with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately.

SKIN CONTACT: Rinse with water.

INGESTION: IF SWALLOWED: Seek medical attention immediately. Call a poison control center or doctor for treatment advice. Have person sip a glass of water if able to swallow. Never give anything by mouth to an unconscious person.

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 4035

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Stop source of spill. Sweep solid material into a suitable container and dispose of in a manner consistent with applicable regulations.

WASTE DISPOSAL METHOD: Dispose of in accordance with applicable Federal, State, and local regulations. Under RCRA regulations, it is the responsibility of the product user to determine, at the time of disposal, whether a material is hazardous.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Store in a dry, cool place away from heat or open flame. Do not store at temperatures above 110 F. Keep container closed when not in use.

OTHER PRECAUTIONS: Follow label instructions. KEEP OUT OF REACH OF CHILDREN.

===== SECTION VIII - PERSONEL SAFETY MEASURES =====

RESPIRATORY PROTECTION: None required in excess of normal ventilation.

VENTILATION: Local mechanical exhaust to provide normal ventilation.

PROTECTIVE GLOVES: None required, except for continuous occupational exposure. For such case use nitrile or neoprene gloves.

EYE PROTECTION: Not required, but contact with eyes must be avoided.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: None required.

WORK/HYGIENIC PRACTICES: None required.

===== SECTION IX - REGULATORY INFORMATION =====

TOXIC SUBSTANCES CONTROL ACT (TSCA): All chemical components in this product are listed on the TSCA Inventory List, or are exempt from listing.

SARA Section 312 HAZARD CATEGORIES: Fire Hazard X Reactivity Hazard
Acute Health Hazard X Chronic Health Hazard X Pressure Hazard

SARA Section 313 REPORTABLE COMPONENTS: (See Section II, If Applicable)

===== SECTION X - SHIPPING INFORMATION =====

DOT SHIPPING NAME: ORM-D Consumer Commodity

DOT HAZARD CLASS: Not Applicable

UN NUMBER: Not Applicable

DOT PACKING GROUP: Not Applicable

SPECIAL SHIPPING INFORMATION: Regulated only when offered for transportation by aircraft.

===== DISCLAIMER =====

The information on this Material Safety Data Sheet represents our current available data and best opinion as to the proper handling in use of this product under normal conditions. Any use of this product which is not in conformance with this Data Sheet or which involves using this product in combination with other materials, or

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 4035

processes is the sole responsibility of the user.