

M A T E R I A L S A F E T Y D A T A S H E E T

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 5697

PRODUCT NAME: SLIP-NOT CLEAR (A/12)
 PRODUCT CODE: 5697

HMIS CODES: H C F R P
 2 4 0 I

WHMIS CLASS: A & B, 5 & D, 2, B

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: ATCO International
 ADDRESS : 2136 Kingston Court
 Marietta, GA 30067-8902
 INFORMATION PHONE : (770)424-7550

DATE PRINTED: 2/9/2007

PREPARED BY: MAURICIO A. AMAYA, DIRECTOR OF TECHNICAL SERVICES
 REVISION DATE: 08/23/2005

===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

| REPORTABLE COMPONENTS | CAS NUMBER | PEL | TLV | WEIGHT PERCENT |
|-----------------------|------------|---------|---------|----------------|
| *XYLENE | 1330-20-7 | 150ppm | 100ppm | 10-20% |
| ACETONE | 67-64-1 | 1000ppm | 1000ppm | 20-40% |
| LPG PROPELLANT | 68476-85-7 | 1000ppm | 1000ppm | 20-40% |
| SILICA | 7631-86-9 | ND | 6mg/m3 | 1-5% |
| TITANIUM DIOXIDE | 13463-67-7 | ND | 10mg/m3 | 1-10% |
| *Toluene | 108-88-3 | 150ppm | 100ppm | 10-20% |
| CLAY | 1332-58-7 | ND | 15mg/m3 | 1-10% |

* Indicates toxic chemical subject to the reporting requirements of SARA Title III, Sec. 313

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: -13 F to 232 F SPECIFIC GRAVITY (H2O=1): 0.80
 VAPOR DENSITY: ND EVAPORATION RATE: ND
 DENSITY: 6.676 lb/gl MATERIAL V.O.C.: 77%
 SOLUBILITY IN WATER: INSOLUBLE. pH (Concentrate): NA
 APPEARANCE: CLEAR, SLIGHTLY AMBER LIQUID. pH (Diluted): NA
 ODOR: SOLVENT-LIKE.

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

OSHA FLAMMABILITY CLASSIFICATION: EXTREMELY FLAMMABLE AEROSOL
 FLASH POINT: 45 F (CONC. ONLY) METHOD USED: TCC
 FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: ND UPPER: ND
 EXTINGUISHING MEDIA: Water fog, Carbon dioxide, Dry chemical, or Foam.

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 5697

SPECIAL FIREFIGHTING PROCEDURES: Hazardous decomposition products may form from incomplete combustion. Wear full protective clothing and self-contained positive pressure breathing apparatus. Cool fire exposed containers to prevent rupturing.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Extremely flammable liquid and vapors. Containers can build pressure from heat and rupture explosively. Volatile vapors can burn in the open or explode if confined. Vapor is heavy and can travel long distances to source of ignition.

===== SECTION V - REACTIVITY DATA =====

STABILITY: Product is stable under normal conditions.

CONDITIONS TO AVOID: Open flame, sparks, or high temperature

INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizing agents.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Thermal decomposition and or burning may produce oxides of carbon and various hydrocarbons.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

===== SECTION VI - HEALTH HAZARD DATA =====

PRIMARY ROUTES OF ENTRY: Inhalation X Eye Contact X
Skin Contact X Ingestion

EXPOSURE LIMIT: Refer to Section II for PEL / TLV exposure limits.

ACUTE EFFECTS OF OVEREXPOSURE

INHALATION: Inhalation of mist can cause irritation of nasal and respiratory passages. Abusive or excessive inhalation may cause irritation to upper respiratory tract, dizziness, nausea and other central nervous system effects.

EYE CONTACT: Can cause severe irritation, redness, tearing and blurred vision.

SKIN CONTACT: Prolonged or frequently repeated skin contact may cause allergic reactions, redness, drying or possible cracking.

SKIN ABSORPTION: Can be irritating to skin

INGESTION: Can cause gastrointestinal irritation, nausea, vomiting, and diarrhea. Aspiration of product into lungs can cause chemical pneumonia.

CHRONIC EFFECTS OF OVEREXPOSURE: Repeated excessive exposures to this product may cause central nervous system, liver, and kidney effects and respiratory or eye irritation.

CARCINOGENICITY: NTP CARCINOGEN: IARC MONOGRAPHS: OSHA REGULATED:

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY OVEREXPOSURE: Pre-existing sensitivity to solvents can cause a heightened reaction by exposure to this product. Pre-existing liver and/or kidney disorders.

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: Remove to fresh air immediately. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical aid immediately.

EYE CONTACT: Immediately flush eyes with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately.

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 5697

SKIN CONTACT: Wash exposed area thoroughly with soap and water. Consult a physician if irritation develops.

INGESTION: Do not induce vomiting. Seek medical attention immediately.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove all ignition sources. Avoid breathing vapors. Shut off source of spill if it can be done safely. Use non-sparking tools. Absorb with inert, absorbant material and dispose of in accordance with applicable regulations.

WASTE DISPOSAL METHOD: Dispose of in accordance with applicable Federal, State, and local regulations. Under RCRA regulations, it is the responsibility of the product user to determine, at the time of disposal, whether a material is hazardous.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Store in a dry, cool place away from heat or open flame. Do not store at temperatures above 120 F.

OTHER PRECAUTIONS: Follow label instructions. KEEP OUT OF REACH OF CHILDREN.

===== SECTION VIII - PERSONEL SAFETY MEASURES =====

RESPIRATORY PROTECTION: None needed unless ventilation is not adequate to reduce vapors below TLV levels. If needed, use a NIOSH approved respirator with an organic vapor cartridge.

VENTILATION: Use with adequate ventilation. Provide general local exhaust ventilation to keep the air contaminant concentration below the applicable exposure limit (OSHA PEL) of the combined components listed in Section II and below the LEL in Section IV.

PROTECTIVE GLOVES: Impervious gloves recommended.

EYE PROTECTION: Safety eye protection to protect against splash of liquids and also aerosol size particles is recommended.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: None required.

WORK/HYGIENIC PRACTICES: Wash thoroughly after handling.

===== SECTION IX - REGULATORY INFORMATION =====

TOXIC SUBSTANCES CONTROL ACT (TSCA): All chemical components in this product are listed on the TSCA Inventory List, or are exempt from listing.

SARA Section 312 HAZARD CATEGORIES: Fire Hazard X Reactivity Hazard

Acute Health Hazard X Chronic Health Hazard X Pressure Hazard X

SARA Section 313 REPORTABLE COMPONENTS: (See Section II, If Applicable)

===== SECTION X - SHIPPING INFORMATION =====

DOT SHIPPING NAME: ORM-D Consumer Commodity

DOT HAZARD CLASS: Not Applicable

UN NUMBER: Not Applicable

DOT PACKING GROUP: Not Applicable

SPECIAL SHIPPING INFORMATION: Regulated only when offered for transportation by aircraft.

===== DISCLAIMER =====

The information on this Material Safety Data Sheet represents our current available data and best opinion as to the proper handling in use of this product under normal conditions. Any use of this product which is not in conformance with this Data Sheet or which involves using this product in combination with other materials, or processes is the sole responsibility of the user.