

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 6500

===== SECTION V - REACTIVITY DATA =====

STABILITY: Product is stable under normal conditions.

CONDITIONS TO AVOID: Avoid heat and mixing with other chemicals.

INCOMPATIBILITY (MATERIALS TO AVOID): Do not mix with acids, ammonia or any organic material.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Thermal decomposition and or burning may produce oxides of carbon, hydrogen chloride gas.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

===== SECTION VI - HEALTH HAZARD DATA =====

PRIMARY ROUTES OF ENTRY: Inhalation X Eye Contact X
Skin Contact X Ingestion

EXPOSURE LIMIT: Refer to Section II for PEL / TLV exposure limits.

ACUTE EFFECTS OF OVEREXPOSURE

INHALATION: Inhalation of fumes or mist can result in irritation or burns to the upper respiratory tract and lungs, pulmonary edema can also occur.

EYE CONTACT: May cause permanent eye injury or blindness.

SKIN CONTACT: Causes moderate to severe burns which may not be immediately painful or visible.

SKIN ABSORPTION: Product is very corrosive to skin.

INGESTION: Harmful if swallowed. Corrosive effects. Can cause severe burns and complete tissue perforation of mucous membranes of mouth, throat and stomach.

CHRONIC EFFECTS OF OVEREXPOSURE: Chronic effects and medical conditions aggravated by overexposure to this product have not been established. Unnecessary exposure to this product or any chemical should be avoided.

CARCINOGENICITY: NTP CARCINOGEN: IARC MONOGRAPHS: OSHA REGULATED:

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY OVEREXPOSURE: No additional effects of overexposure to this material can be found from available information.

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: Remove to fresh air immediately. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical aid immediately.

EYE CONTACT: Flush eyes with cool running water for 15 minutes while calling for IMMEDIATE MEDICAL ATTENTION. Washing eyes within several seconds is essential to achieve maximum effectiveness.

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 6500

SKIN CONTACT: In case of contact, immediately flush skin with soap and plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Wash and thoroughly clean contaminated clothing and shoes before reuse. Get medical attention.

INGESTION: IF SWALLOWED: Call a physician immediately. Do NOT induce vomiting unless directed to do so by a physician. Never give anything by mouth to an unconscious person.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Stop source of spill. Absorb with inert absorbant material and dispose of in a manner consistent with applicable regulations.

WASTE DISPOSAL METHOD: Dispose of in accordance with applicable Federal, State, and local regulations. Under RCRA regulations, it is the responsibility of the product user to determine, at the time of disposal, whether a material is hazardous.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Do not store above 120 F. Keep closure tight and container upright to prevent leakage. Store drum out of sunlight and away from heat, sparks, or flame. Store only in well-ventilated areas.

OTHER PRECAUTIONS: Follow label instructions. KEEP OUT OF REACH OF CHILDREN.

===== SECTION VIII - PERSONEL SAFETY MEASURES =====

RESPIRATORY PROTECTION: Wear an appropriate, properly fitted vapor respirator during application of this product in a confined space.

VENTILATION: Sufficient, in volume and pattern, to keep workroom concentration below current applicable OSHA safety and health requirements.

PROTECTIVE GLOVES: Impervious gloves recommended.

EYE PROTECTION: Use safety eyewear designed to protect against splash of liquids.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Synthetic apron to protect against splash of liquids.

WORK/HYGIENIC PRACTICES: Wash thoroughly after handling.

===== SECTION IX - REGULATORY INFORMATION =====

TOXIC SUBSTANCES CONTROL ACT (TSCA): All chemical components in this product are listed on the TSCA Inventory List, or are exempt from listing.

SARA Section 312 HAZARD CATEGORIES: Fire Hazard X Reactivity Hazard X

Acute Health Hazard X Chronic Health Hazard Pressure Hazard

SARA Section 313 REPORTABLE COMPONENTS: (See Section II, If Applicable)

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 6500

===== SECTION X - SHIPPING INFORMATION =====

DOT SHIPPING NAME: Hypochlorite Solution

DOT HAZARD CLASS: Class 8

UN NUMBER: UN 1791

DOT PACKING GROUP: Group III

SPECIAL SHIPPING INFORMATION: Check for compatibility with other materials shipped.

===== DISCLAIMER =====

The information on this Material Safety Data Sheet represents our current available data and best opinion as to the proper handling in use of this product under normal conditions. Any use of this product which is not in conformance with this Data Sheet or which involves using this product in combination with other materials, or processes is the sole responsibility of the user.