

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 6492

SPECIAL FIREFIGHTING PROCEDURES: Wear self contained breathing apparatus when indicated.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Contents under pressure. Exposure to temperatures above 120F may cause bursting.

===== SECTION V - REACTIVITY DATA =====

STABILITY: Product is stable under normal conditions.

CONDITIONS TO AVOID: Temperatures above 120F. Hot surfaces.

INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizers, acids, alkalies

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Thermal decomposition and burning may produce carbon dioxide and carbon monoxide.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

===== SECTION VI - HEALTH HAZARD DATA =====

PRIMARY ROUTES OF ENTRY: Inhalation X Eye Contact
Skin Contact X Ingestion X

EXPOSURE LIMIT: Refer to Section II for PEL / TLV exposure limits.

ACUTE EFFECTS OF OVEREXPOSURE

INHALATION: May cause light headedness, or dizziness.

EYE CONTACT: May cause irritation.

SKIN CONTACT: May cause slight irritation.

INGESTION: May cause nausea.

CHRONIC EFFECTS OF OVEREXPOSURE: Contains 2-butoxyethanol, which can cause liver or kidney damage if absorbed thru the skin in large amounts.

CARCINOGENICITY: NTP CARCINOGEN: IARC MONOGRAPHS: OSHA REGULATED:

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: None

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: Remove to fresh air.

EYE CONTACT: Flush eyes with cool running water for 15 minutes.

SKIN CONTACT: Wash with soap and water.

INGESTION: IF SWALLOWED: Drink large quantity of water. In all instances, consult a physician if irritation persists.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Mop or wipe up spill. Dispose of residue in accordance with federal, state, and local guidelines.

WASTE DISPOSAL METHOD: Wrap container and place in trash collection. Do not puncture or incinerate container.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Store in a cool, dry area. Keep away from heat, flames or sparks.

24-hour Emergency Phone: (800)255-3924

PRODUCT CODE: 6492

OTHER PRECAUTIONS: Follow label instructions. KEEP OUT OF REACH OF CHILDREN.
Exposure to temperatures above 120F may cause bursting.

===== SECTION VIII - PERSONEL SAFETY MEASURES =====

RESPIRATORY PROTECTION: Not usually required.

VENTILATION: Local mechanical exhaust to provide normal ventilation.

PROTECTIVE GLOVES: Not usually required, but avoid contact with skin.

EYE PROTECTION: Use safety eyewear designed to protect against splash of liquids.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Not usually required.

WORK/HYGIENIC PRACTICES: Wash hands thoroughly after handling.

===== SECTION IX - REGULATORY INFORMATION =====

TOXIC SUBSTANCES CONTROL ACT (TSCA): All chemical components in this product are listed on the TSCA Inventory List, or are exempt from listing.

SARA Section 312 HAZARD CATEGORIES: Fire Hazard___ Reactivity Hazard___

Acute Health Hazard_X_ Chronic Health Hazard_X_ Pressure Hazard___

SARA Section 313 REPORTABLE COMPONENTS: (See Section II, If Applicable)

===== SECTION X - SHIPPING INFORMATION =====

DOT SHIPPING NAME: ORM-D Consumer Commodity

DOT HAZARD CLASS: None

UN NUMBER: NA

DOT PACKING GROUP: NA

SPECIAL SHIPPING INFORMATION: NA

===== DISCLAIMER =====

The information on this Material Safety Data Sheet represents our current available data and best opinion as to the proper handling in use of this product under normal conditions. Any use of this product which is not in conformance with this Data Sheet or which involves using this product in combination with other materials, or processes is the sole responsibility of the user.